
JOB # 25

NORTH DAKOTA

DEPARTMENT OF TRANSPORTATION

H-5-094(118)001

Golden Valley **Beach Visitor Center** Chip Seal



GOVERNING SPECIFICATIONS:

2014 Standard Specifications adopted by the North Dakota Department of Transportation and the Supplemental Specifications effective on the date the project is advertised.

PROJECT NUMBER \ DESCRIPTION **NET MILES** H-5-094(118)001 \ Chip Seal

N/A


GROSS MILES N/A





DESIGNERS

Jason Fischer /s/



STATE COUNTY MAP

01/29/16

Lawrence Gangl /s/

Dickinson District Engineer
ND DEPARTMENT OF TRANSPORTATION

APPROVED DATE

I hereby certify that the attached plans were prepared by me or under my direct supervision and that I am a duly registered professional engineer under the laws of the state of ND.

APPROVED DATE _ 01/29/16

Rob Rayhorn /s/ Assistant District Engineer

This document was originally issued and sealed by Rob Rayhorn Registration Number PE- 4289, on 01/29/16 and the original document is stored at the North Dakota Department of Transportation

TABLE OF CONTENTS

STATE	PROJECT NO.	SECTION NO.	SHEET NO.
ND	H-5-094(118)001	2	1

PLAN SECTIONS

LIST OF STANDARD DRAWINGS

Section	Page(s)	Description	Number	Description	
1	1	Title Sheet	D-101-1, 2,3	NDDOT Abbreviations	
2	1	Table of Contents	D-101-10	NDDOT Utility Company and Organization Abbreviations	
6	1	Notes	D-101-20, 21	Line Styles	
8	1	Quantities	D-101-30, 31,32	Symbols	
10	1	Basis of Estimate	D-704-7	Breakaway Systems for Construction Zone Signs - Perforated Tube	
20	1	General Details	D-704-8	Breakaway Systems for Construction Zone Signs - U-Channel Post	
100	1-2	Work Zone Traffic Control	D-704-9	Construction Sign Details - Terminal and Guide Signs	
120	1	Pavement Marking	D-704-10	Construction Sign Details - Regulatory Signs	
			D-704-11	Construction Sign Details - Warning Signs	
			D-704-13	Barricade and Channelizing Device Details	
			D-704-14	Construction Sign Punching and Mounting Details	
			D-704-15	Road Closure Layouts	
			D-704-22	Construction Truck and Temporary Detour Layouts	
			D-704-26	Miscellaneous Sign Layouts	
			D-762-4	Pavement Marking	

1/28/2016 8:31:19 AM jrfischer

|--|

STATE	PROJECT NO.	SECTION NO.	SHEET NO.
ND	H-5-094(118)001	6	1

100-P01	TIED PROJECT: This project is tied to projects SOIB-5-016(024)060, SOIB-5-021(024)052 and SOIB-5-008(047)012. Flagging signs shown in detail 704-15 (Type A) and stop sign and truck entering signs shown in detail 704-22 (Type K) will be used on all projects, but paid for once on project SOIB-5-008(047)012
100-P02	TIED PROJECT: Include Contract Bond and Mobilization costs in tied project SOIB-5-008(047)012
107-710	HAUL ROADS: Before submitting a proposal, contact the appropriate State, County, Township, or City officials to determine if there are any roadways that will be designated as "no haul routes".

TRAFFIC CONTROL FOR SEALCOAT: Traffic control for the chip seal consists of closing the visitor center while work is taking place. The visitor center can be closed for two days for the seal coat operation and another two days after the maintenance period for the final sweeping and permanent striping operation.

Maintain traffic during the maintenance period. During this time, install and maintain Fresh Oil Loose Rock W20-52-54 signs at both entrances to the visitor center parking lot.

The required traffic control signs and devices are included in the "Traffic Control Devices" List.

This document was originally issued and sealed by Jason R. Fischer, Registration Number PE-6865, on 01/29/16 and the original document is stored at the North Dakota Department of Transportation.

ESTIMATE OF QUANTITIES

STATE	PROJECT NO.	SECTION NO.	SHEET NO.
ND	H-5-094(118)001	8	1

SPEC CODE ITEM DESCRIPTION	UNIT	MAINLINE	TOTAL	i
420 0111 CRS2P EMULSIFIED ASPHALT	GAL	4,391	4,391	ı
420 0125 COVER COAT MATERIAL CL 41	TON	145	145	1
704 1000 TRAFFIC CONTROL SIGNS	UNIT	196	196	i
704 1052 TYPE III BARRICADE	EA	8	8	i
762 1104 PVMT MK PAINTED 4IN LINE	LF	4,403	4,403	

STATE	PROJECT NO.	SECTION NO.	SHEET NO.
ND	H-5-094(118)001	10	1

		Beach Visitor Center		
Material	aterial Unit		Quantity	
Waterial	Oill	(SY)		
CRS2P @ 0.38 Gal/SY	Gal	11,556	4391	
Cover Coat CL 41 @ 25 lbs/SY	Ton	11,556	145	

Location - Type	Quantity
White – Pavement Marking Painted 4 IN	
Line	4192 LF
Blue – Pavement Marking Painted 4 IN	
Line	211 LF

This document was originally issued and sealed by Jason R. Fischer, Registration Number PE-6865, on 01/29/16 and the original document is stored at the North Dakota Department of Transportation.

Basis of Estimate Beach Visitor Center

	<u> </u>		0507151	
	ND STATE	PROJECT NO. H-5-094(118)00	section NO.	SHEET NO.
BEACH NO VISITOR CENTER BEACH NO TO THE TO	ND 420-125 CO	Estimate of Quantities OVERCOAT MATERIAL CRS2P EMULSIFIED ASPH	This document was of issued and seale Jason R. Fisch Registration Num PE- 6865, on 01/29/16 and the document is stored North Dakota Deparation of Transportation	originally d by er hber e original at the rtment

ND	H-5-094(118)001	100	1
OTAIL	TROSECT NO.	NO.	NO.
STATE	PROJECT NO.	SECTION	SHEET

SIGN NUMBER	SIGN SIZE	DESCRIPTION	AMOUNT REQUIRED	UNITS PER AMOUNT	UNITS SUB TOTAL
D3-36	36"x6"	STREET NAME SIGN (Sign and installation only)		6	
G20-1-60	60"x24" 60"x24"	ROAD WORK NEXT MILES		34	
G20-1b-60 G20-2-48	48"x24"	WORK IN PROGRESS/ NO WORK IN PROGRESS (Sign and installation only) END ROAD WORK		26 19	
G20-2-46 G20-4-36	36"x18"	PILOT CAR FOLLOW ME (Mounted to back of pilot car)		18	
G20-10-108	108"x48"	CONTRACTOR SIGN		64	
G20-50a-72	72"x36"	ROAD WORK NEXT MILES RT & LT ARROWS		37	
G20-52a-72	72"x24"	ROAD WORK NEXT MILES RT or LT ARROW		30	
G20-55-96	96"x48"	SPEED LIMIT ENFORCED - MINIMUM FEE \$80 WHEN WORKERS PRESENT		59	
M1-1-36	36"x36"	INTERSTATE ROUTE MARKER (Post and installation only)		10	
M1-4-24 M1-5-24	24"x24" 24"x24"	U.S. ROUTE MARKER (Post and installation only) STATE ROUTE MARKER (Post and installation only)		10 10	
M3-1-24	24 x24 24"x12"	NORTH (Mounted on route marker post)		7	
M3-2-24	24"x12"	EAST (Mounted on route marker post)		7	
M3-3-24	24"x12"	SOUTH (Mounted on route marker post)		7	
M3-4-24	24"x12"	WEST (Mounted on route marker post)		7	
M4-8-24	24"x12"	DETOUR (Mounted on route marker post)		7	
M4-9-30	30"x24"	DETOUR ARROW RIGHT or LEFT/AHD AND RT or LT		15	
M4-10-48	48"x18"	DETOUR ARROW RIGHT or LEFT		23	
M5-1-21 M5-2-21	21"x15" 21"x15"	ARROW AHD AND RT or LT(Mounted on route marker post) ARROW AHD UP & RT or LT (Mounted on route marker post)		7	
M6-1-21	21"x15"	ARROW RT or LT (Mounted on route marker post)		7	
M6-2-21	21"x15"	ARROW UP & RT or LT (Mounted on route marker post)		7	
M6-3-21	21"x15"	ARROW AHD (Mounted on route marker post)		7	
R1-1-48	48"x48"	STOP		32	
R1-1a-18	18"x18"	STOP and SLOW PADDLE Back to Back		5	
R1-2-60	60"x60"	YIELD		29	
R2-1-48	48"x60" 24"x18"	SPEED LIMIT		39 10	
R2-1a-24 R3-7-48	48"x48"	MINIMUM FEE \$80 (Mounted on Speed Limit post) LEFT or RIGHT LANE MUST TURN LEFT or RIGHT		35	
R4-1-48	48"x60"	DO NOT PASS		39	
R4-7-48	48"x60"	KEEP RIGHT SYMBOL		39	
R5-1-48	48"x48"	DO NOT ENTER		35	
R6-1-36	36"x12"	ONE WAY RIGHT or LEFT		13	
R7-1-12	12"x18"	NO PARKING		11	
R10-6-24	24"x36"	STOP HERE ON RED		16	_
R11-2-48	48"x30"	ROAD CLOSED	2	28	5
R11-2a-48 R11-3a-60	48"x30" 60"x30"	STREET CLOSED ROAD CLOSED MILES AHEAD LOCAL TRAFFIC ONLY		28 31	
R11-3c-60	60"x30"	STREET CLOSED MILES AHEAD LOCAL TRAFFIC ONLY		31	
R11-4a-60	60"x30"	STREET CLOSED TO THRU TRAFFIC		31	
W1-3-48	48"x48"	RIGHT or LEFT SHARP REVERSE CURVE ARROW		35	
W1-4-48	48"x48"	RIGHT or LEFT REVERSE CURVE ARROW		35	
W1-4b-48	48"x48"	DOUBLE RIGHT or LEFT REVERSE CURVE ARROW		35	
W1-6-48	48"x24"	LARGE ARROW		26	
W3-1-48 W3-3-48	48"x48" 48"x48"	STOP AHEAD SYMBOL SIGNAL AHEAD SYMBOL		35 35	
W3-4-48	48"x48"	BE PREPARED TO STOP		35	
W3-5-48	48"x48"	SPEED REDUCTION AHEAD		35	
W4-2-48	48"x48"	RIGHT or LEFT LANE TRANSITION SYMBOL		35	
W5-1-48	48"x48"	ROAD NARROWS		35	
W5-8-48	48"x48"	THRU TRAFFIC RIGHT LANE		35	
W5-9-48	48"x48"	ROAD WORK TRAFFIC ONLY DOWN & LT or RT ARROW		35	
W6-3-48	48"x48" 48"x48"	TWO WAY TRAFFIC SYMBOL		35	
W8-1-48 W8-3-48	48"x48" 48"x48"	BUMP PAVEMENT ENDS		35 35	
W8-7-48	48"x48"	LOOSE GRAVEL		35	
W8-9a-48	48"x48"	SHOULDER DROP-OFF		35	
W8-11-48	48"x48"	UNEVEN LANES		35	
W8-12-48	48"x48"	NO CENTER STRIPE		35	
W8-53-48	48"x48"	TRUCKS ENTERING HIGHWAY		35	
W8-54-48	48"x48"	TRUCKS ENTERING AHEAD or FT.	2	35	7
W8-55-48	48"x48"	TRUCKS CROSSING AHEAD or FT.		35	
W8-56-48 W9-3a-48	48"x48" 48"x48"	TRUCKS EXITING HIGHWAY CENTER LANE CLOSED SYMBOL		35 35	
W12-2-48	46 x46 48"x48"	LOW CLEARANCE SYMBOL		35	
W13-1-24	24"x24"	MPH ADVISORY SPEED PLATE (Mounted on warning sign post)		11	
W13-4-48	48"x60"	RAMP ARROW		39	
W14-3-48	48"x36"	NO PASSING ZONE		23	
W20-1-48	48"x48"	ROAD WORK AHEAD or _FT or _ MILE		35	
W20-2-48	48"x48"	DETOUR AHEAD or FT		35	
W20-3-48	48"x48"	ROAD or STREET CLOSED AHEAD or FT.		35	
W20-4-48	48"x48"	ONE LANE ROAD AHEAD or FT.		35	-
W20-5-48 W20-7a-48	48"x48" 48"x48"	RIGHT OF LEFT LANE CLOSED AHEAD OF FT.		35	-
W20-7a-48 W20-7k-24	48"x48" 24"x18"	FLAGGING SYMBOLFEET (Mounted on warning sign post)		35 10	
W20-7K-24 W20-8-48	48"x48"	STREET CLOSED		35	
W20-51-48	48"x48"	EQUIPMENT WORKING		35	
W20-51-48	54"x12"	NEXTMILES (Mounted on warning sign post)		12	
W21-1a-48	48"x48"	WORKERS SYMBOL		35	
W21-2-48	48"x48"	FRESH OIL		35	
W21-3-48		ROAD MACHINERY AHEAD or FT			

SIGN NUMBER	SIGN SIZE	DESCRIPTION	AMOUNT REQUIRED	UNITS PER AMOUNT	UNITS SUB TOTAL
W21-5-48	48"x48"	SHOULDER WORK		35	
W21-5a-48	48"x48"	RIGHT or LEFT SHOULDER CLOSED		35	
W21-5b-48	48"x48"	RIGHT or LEFT SHOULDER CLOSED AHEAD or FT.		35	
W21-6a-48	48"x48"	SURVEY CREW AHEAD		35	
W21-50-48	48"x48"	BRIDGE PAINTING AHEAD or FT.		35	
W21-51-48	48"x48"	MATERIAL ON ROADWAY		35	
W22-8-48	48"x48"	FRESH OIL LOOSE ROCK	2	35	70
	24"x24"	TAKE TURNS (6" D letters) (Mounted on stop sign post)		11	
	1				

SPECIAL SIG	NS		

SPEC & CODE

704-1000 TRAFFIC CONTROL SIGNS TOTAL UNITS 196

SPEC & DESCRIPTION UNIT QUANTITY CODE 704-0100 FLAGGING 704-1041 ATTENUATION DEVICE-TYPE B-55 MHR EACH 704-1043 ATTENUATION DEVICE-TYPE B-65 EACH 704-1044 ATTENUATION DEVICE-TYPE B-70 EACH 704-1050 TYPE I BARRICADES EACH 704-1050 TYPE II BARRICADES
704-1052 TYPE III BARRICADES EACH EACH 704-1060 DELINEATOR DRUMS 704-1065 TRAFFIC CONES EACH EACH 704-1067 TUBULAR MARKERS
704-1070 DELINEATOR
704-1072 FLEXIBLE DELINEATORS EACH EACH EACH 704-1081 VERTICAL PANELS - BACK TO BACK EACH 704-1085 SEQUENCING ARROW PANEL - TYPE A EACH 704-1086 SEQUENCING ARROW PANEL - TYPE B EACH 704-1087 SEQUENCING ARROW PANEL - TYPE C 704-1088 SEQUENCING ARROW PANEL - TYPE C - CROSSOVER EACH EACH 704-1095 TYPE B FLASHERS EACH 704-1500 OBLITERATION OF PVMT MK 704-3501 PORTABLE PRECAST CONCRETE MED BARRIER 704-3510 PRECAST CONCRETE MED BARRIER - STATE FURNISHED EACH 762-0200 RAISED PAVEMENT MARKERS EACH 762-0420 SHORT TERM 4IN LINE - TYPE R 762-0430 SHORT TERM 4IN LINE - TYPE NR 772-2110 FLASHING BEACON - POST MOUNTED EACH

NOTE:
If additional signs are
required, units will be
calculated using the formula
from Section III-19.06 of the
Design Manual.
http://www.dot.nd.gov/


This document was originally issued and sealed by Jason R. Fischer, Registration Number PE-6865, on 1/29/16 and the original document is stored at the North Dakota Department of Transportation.

Traffic Control Devices List

1/27/2016 3:02 PM R:\project\50094001.118\district\100WZ_001_TCDL.xlsm VERSION: 4.4.2008

SECTION NO. SHEET NO. STATE PROJECT NO. ND H-5-094(118)001 100 2 TRUCKS ENTERING AHEAD W8-54-48 FRESH OIL LOOSE ROCK W22-8-48 ROAD CLOSED R11-2-48 Barricade mounted ND 16 Beach Visitor Center FRESH OIL LOOSE ROCK W22-8-48 This document was originally issued and sealed by Jason R. Fischer Registration Number ROAD CLOSED PE- 6865, on 01/29/16 and the original document is stored at the R11-2-48 TRUCKS ENTERING AHE AD Barricade mounted North Dakota Department of Transportation W8-54-48 Traffic Control Beach Visitor Center 1/27/2016 3:04:22 PM R:\project\50094001.118\district\100WZ_002_ConSign.dgn jrfischer

STATE	PROJECT NO.	SECTION NO.	SHEET NO.
ND	H-5-094(118)001	120	1



Use spotting tabs to mark the location of the existing striping prior to applying seal coat. Line lengths and dimesions are for estimating purposes. Striping will be field measured. Place permanent striping in its original location with the following exception:

** Extend existing gore area 10' to the south.

Estimate of Quantities

Pavement MK 4IN Line (white) - 4192 LF Pavement MK 4IN Line (blue) - 211 LF

This document was originally issued and sealed by Jason R. Fischer Registration Number PE- 6865, on 01/29/16 and the original document is stored at the North Dakota Department of Transportation

Striping Layout

Beach Visitor Center

?	This is a special text character used in the labeling	BV	butterfly valve	Ct	Court	ES	end section	
	of existing features. It indicates a feature that has	Вур	bypass	Xarm	cross arm	Engr	eng i neer	
	an unknown characteristic, potentially based on: lack of description, location accuracy or purpose.	C Gdrl	cable guardrail	Xbuck	cross buck	ESS	environmental sensor st	.ation
	lack of description, location accuracy of purpose.	Calc	calculate	Xsec	cross sections	Eq	equal	
Abn	abandoned	Cd	candela	Xing	crossing	Eq	equat i on	
Abut	abutment	CIP	cast iron pipe	Xrd	Crossroad	Evgr	evergreen	
Ac	acres	СВ	catch basin	Crn	crown	Exc	excavation	
Adj	adjusted	CRS	cationic rapid setting	CF	cubic feet	Exst	existing	
Aggr	aggregate	C Gd	cattle guard	M3	cubic meter	Exp	expansion	
Ahd	ahead	C To C	center to center	M3/s	cubic meters per second	Expy	Expressway	
ARV	air release valve	Cl or €	centerline	CY	cubic yard	E .	external of curve	
Align	alignment	Cm	centimeter	Cy/mi	cubic yards per mile	Extru	extruded	
Al	alley	Ch	chain	Culv	culvert	FOS	factor of safety	
Alt	alternate	Chnlk	chain-link	C&G	curb & gutter	F	Fahrenheit	
Alum	aluminum	Ch Blk	channel block	CI	curb inlet	FS	far side	
ADA	Americans with Disabilities Act	Ch Ch	channel change	CR	curb ramp	F	farad	
A	ampere	Chk	check	CS	curve to spiral	Fed	Federal	
&	and	Chsld	chiseled	C	cut	FP	feed point	
Appr	approach	Cir	circle	Dd Ld	dead load	Ft	feet/foot	
Approx	approximate	CI	class	Defl	deflection	Fn	fence	
ACP	asbestos cement pipe	Cl	clay	Defm	deformed	 Fn P	fence post	
Asph	asphalt	CIF	clay fill	Deg or D	degree	FO	fiber optic	
AC	asphalt cement	CI Hvy	clay heavy	Dint	delineate	FB	field book	
Assmd	assumed	CI Lm	clay loam	Dintr	delineator	FD	field drive	
	at	CInt	clean-out	Depr	depression	F	fill	
@ Atten	attenuation	Clr	clear	Desc	description	FAA	••••	3.7
Atten	automatic traffic recorder			Desc	detail	FS	fine aggregate angularity fine sand	У
		CI&gr Co S	clearing & grubbing coal slack	DWP		FH		
Ave	Avenue		combination		detectable warning panel		fire hydrant	
Avg	average	Comb.		Dtr Die	detour	FI	flange	
ADT	average daily traffic	Coml	commercial	Dia Dia	diameter	Flrd	flared	
Az	azimuth	Compr	compression	Dir	direction	FES	flared end section	
Bk	back	CADD	computer aided drafting & design	Dist	distance	F Bcn	flashing beacon	
BF	back face	Conc	concrete	DM	disturbed material	FA	flight auger sample	
Bs	backsight	Cond	conductor	DB	ditch block	FL -	flow line	
Balc	balcony	Const	construction	DG	ditch grade	Ftg	footing	
B Wire	barbed wire	Cont	continuous	Dbl	double	FM	force main	
Barr	barricade	CSB	continuous split barrel sample	Dn	down	Fs	foresight	
Btry	battery	Contr	contraction	Dwg	drawing	Fnd	found	
Brg	bearing	Contr	contractor	Dr	drive	Fdn	foundation	
Bl	beehive i nlet	CP	control point	Drwy	driveway	Frac	fractional	
Beg	begin	Coord	coordinate	DI	drop inlet	Frwy	freeway	
BM	bench mark	Cor	corner	D	dry density	Frt	front	
Bkwy	bikeway	Corr	corrected	Ea	each	FF	front face	
Bit	bituminous	CAES	corrugated aluminum end section	Esmt	easement	F Disp	fuel dispenser	
Blk	block	CAP	corrugated aluminum p i pe	Е	East			
Bd Ft	board feet	CMES	corrugated metal end section	EB	Eastbound			
ВН	bore hole	CMP	corrugated metal pipe	Elast	elastomeric		NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
BS	both sides	CPVCP	corrugated poly-vinyl chloride pipe	EL	electric locker		07-01-14	This
Bot	bottom	CSES	corrugated steel end section	E Mtr	electric meter		REVISIONS	is
DI I	Daylayand	000			-141-1		DATE CHANGE	

Elec

EDM

Ellipt

Emb

Emuls

Elev or El

electric/al

elevation

elliptical

embankment

emulsion/emulsified

electronic distance meter

CSP

С

Co

Crse

C Gr

CS

corrugated steel pipe

coulomb

County

course

course gravel

course sand

Blvd

Bndry

Brkwy

ВС

Br

Bldg

Boulevard

boundary

brass cap

breakaway

bridge

building

NORTH DAKOTA				
DEPARTM	IENT OF TRANSPORTATION			
07-01-14				
	REVISIONS			
DATE	CHANGE			

This document was originally issued and sealed by Roger Weigel, Registration Number PE- 2930, on 07/01/14 and the original document is stored at the North Dakota Department of Transportation

NDDOT ABBREVIATIONS

PSD

Pvmt

passing sight distance

pavement

FFP	fuel filler pipes	IPn	Iron Pin	MC	modium auring
FLS	fuel leak sensor	IP		M	medium curing
			iron Pipe		mega
Furn	furnish/ed	Jt	joint	Mer	meridian
Gal	gallon	J	joule	M M/-	meter
Galv	galvan i zed	Jct	junction	M/s	meters per second
Gar	garage	K	kelvin	M	mid ordinate of curve
Gs L	gas line	Kn	kilo newton	Mi	mile
G Reg	gas line regulator	Kpa	kilo pascal	MM	mile marker
GMV	gas main valve	Kg	kilogram	MP	mile post
G Mtr	gas meter	Kg/m3	kilogram per cubic meter	MI	milliliter
GSV	gas service valve	Km	kilometer	Mm	millimeter
GVP	gas vent pipe	K	Kip(s)	Mm/hr	millimeters per hour
GV	gate valve	LS	Land Surveyor (licensed)	Min	minimum
Ga	gauge	LSIT	Land Surveyor In Training	Misc	miscellaneous
Geod	geodetic	Ln	lane	Mon	monument
GIS	Geographical Information System	Lg	large	Mnd	mound
G	giga	Lat	latitude	Mtbl	mountable
GPS	Global Positioning System	Lt	left	Mtd	mounted
Gov	government	L	length of curve	Mtg	mounting
Grd	graded/grade	Lens	lenses	Mk	muck
Gr	gravel	Lvl	level	Mun	municipal
Grnd	ground	LB	level book	N	nano
GWM	ground water monitor	LvIng	leveling	NGS	National Geodetic Survey
Gdrl	guardrail	Lht	light	NS	near side
Gtr	gutter	LP	light pole	Neop	neoprene
H Plg	H piling	Ltg	lighting	Ntwk	network
Hdwl	headwall	Lig Co	lignite coal	N	newton
На	hectare	Lig SI	lignite slack	N	North
Ht	height	LF	linear foot	NE	North East
HI	height of instrument	Liq	liquid	NW	North West
Hel	helical	LL	liquid limit	NB	Northbound
Н	henry	 	litre	No. or #	number
Hz	hertz	Lm	loam	Obsc	obscure(d)
HDPE	high density polyethylene	Loc	location	Obsc	observation
HM		LC	long chord	Ocpd	
HP	high mast				occupied
	high pressure	Long.	longitude	Ocpy	occupy
HPS	high pressure sodium	Lp	loop	Off Loc	office location
Hwy	highway	LD	loop detector	O/s	offset
Hor	horizontal	Lm	lumen	OC	on center
HBP	hot bituminous pavement	Lum	luminaire	C	one dimensional consolidation
HMA	hot mix asphalt	L Sum	lump sum	OC	organic content
Hr	hour(s)	Lx	lux	Orig	original
Hyd	hydrant	ML	main line	O To O	out to out
Ph	hydrogen ion content	M Hr	man hour	OD	outside diameter
l d	identification	MH	manhole	OH	overhead
In or "	inch	Mkd	marked	PMT	pad mounted transformer
Incl	inclinometer tube	Mkr	marker	Pg	pages
IMH	inlet manhole	Mkg	marking	Pntd	painted
ID	inside diameter	MA	mast arm	Pr	pair
Inst	instrument	Matl	material	Pnl	panel
Intchg	interchange	Max	maximum	Pk	park
Intmdt	intermediate	MC	meander corner	PK	Parker-Kalon nail
Intscn	intersection	Meas	measure	Pa	pascal

Mdn

MD

median

median drain

Inv

IM

invert

iron monument

Ped pedestrian PPP pedestrian pushbutton post Pen. penetration perforated Perf Per. perimeter PL pipeline Ы place P&P plan & profile PL plastic limit Ы plate Pt point PCC point of compound curve PC point of curve ΡI point of intersection PRC point of reverse curvature PΤ point of tangent POC point on curve POT point on tangent PΕ polyethylene PVC polyvinyl chloride PCC Portland Cement concrete Lb or # pounds PP power pole Preempt preemption Prefab prefabricated Prfmd preformed Prep preperation Press. pressure PRV pressure relief valve Prestr prestressed Pvt private PD private drive Prod. production/produce Prog programmed Prop. property Prop Ln property line

pedestal

Ped

Ppsd

PB

proposed

pull box

This document was originally issued and sealed by Roger Weigel, Registration Number PE- 2930, on 08/03/15 and the original document is stored at the North Dakota Department of Transportation

NDDOT ABBREVIATIONS D-101-3

Qty quantity SN sign number Tan tangent Qtr Sig Т quarter signal tangent (semi) Si CI TS Rad or R radius silt clay tangent to spiral RR Si CI Lm Tel railroad silty clay loam telephone Si Lm Rlwy railway silty loam Tel B Telephone Booth Rsd raised Sgl single Tel P telephone pole RTP random traverse point SC slow curing Τv television SS slow setting Rge or R Temp temperature range Sm RC rapid curing small Temp temporary S TBM Rec record South temporary bench mark SE South East Rcy Τ tesla recycle SW South West RAP Τ thinwall tube sample recycled asphalt pavement SB **RPCC** recycled portland cement concrete Southbound T/mi tons per mile Ref reference Sp spaces Ts topsoil R Mkr reference marker Spcl special Twp or T township SA RMreference monument special assembly Traf traffic SP Refl reflectorized special provisions **TSCB** traffic signal control box G RCB Tr reinforced concrete box specific gravity trail **RCES** Spk reinforced concrete end section spike Transf transformer RCP SC spiral to curve TB reinforced concrete pipe transit book ST RCPS spiral to tangent Trans transition reinforced concrete pipe sewer SB Reinf reinforcement split barrel sample TT transmission tower Res reservation SH sprinkler head Trans transverse Ret retaining SV sprinkler valve Trav traverse Sq TP Rev square traverse point reverse SF Rt square feet Trtd treated right R/W Km2 Trmt right of way square kilometer treatment Riv M2 Qc triaxial compression river square meter SY Rd **TERO** road square yard tribal employment rights ordinance Rdbd Stk Tpl road bed stake triple TP Std turning point Rdwy roadway standard **RWIS** Ν roadway weather information system standard penetration test Тур typical Rk rock Std Specs standard specifications Qu unconfined compressive strength Rt route Sta station Ugrnd underground Sta Yd USC&G US Coast & Geodetic Survey Salv salvage(d) station yards US Geologic Survey Sd sand Stm L steam line USGS Sdy CI sandy clay SEC steel encased concrete Util utility Sdy CI Lm sandy clay loam SMA stone matrix asphalt VG valley gutter Sdy FI sandy fill SSD stopping sight distance Vap vapor Sdy Lm sandy loam SD storm drain Vert vertical San sanitary sewer line St street VC vertical curve SPP VCP Sc scoria structural plate pipe vitrified clay pipe SPPA Sec seconds structural plate pipe arch ٧ volt Sec section Str structure Vol volume SL Subd subdivision Wkwy walkway section line W Sep separation Sub subgrade water content Sub Prep WGV Seq sequence subgrade preperation water gate valve Serv Ss WL water line service subsoil Sh SE superelevation WM water main shale SS Sht sheet supplement specification WMV water main valve Shtng supplemental sheeting Supp W Mtr water meter surfacing WSV Shldr shoulder Surf water service valve Sw sidewalk Surv survey WW water well S W siemens Sym symmetrical watt SD SI systems international Wrng sight distance wearing

Wb weber WIM weigh in motion W west WB westbound Wrng wiring W/ with W/o without WC witness corner WGS world geodetic system

Z zenith

This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 08/03/15 and the original document is stored at the North Dakota Department of Transportation

NDDOT UTILITY COMPANY AND ORGANIZATION ABBREVIATIONS

702COM 702 Communications **ACCENT** Accent Communications AGASSIZ WU Agassiz Water Users Incorporated

Assiociated General Contractors of America AGC

All PI Alliance Pipeline

ALL SEAS WU All Seasons Water Users Association

AMOCO PI Amoco Pipeline Company AMRDA HESS Amerada Hess Corporation AT&T AT&T Corporation

BPAW

Bear Paw Energy Incorporated

BAKER ELEC Baker Electric **BASIN ELEC**

Basin Electric Cooperative Incorporated **BEK TEL Bek Communications Cooperative BELLE PL** Belle Fourche Pipeline Company

Bureau of Land Management BLM BNSF Burlington Northern Santa Fe Railway

BOEING Boeing

BRNS RWD Barnes Rural Water District **BURK-DIV ELEC** Burke-Divide Electric Cooperative

Burleigh Water Users BURL WU

Cable One Cable One CABLE SERV Cable Services

CAP ELEC Capital Electric Cooperative Incorporat CASS CO ELEC Cass County Electric Cooperative **CASS RWU** Cass Rural Water Users Incorporated **CAV ELEC** Cavalier Rural Electric Cooperative

CBLCOM Cablecom Of Fargo **CENEX PL** Cenex Pipeline

CENT PL WATER DIST Central Pipe Line Water District **CENT PWR ELEC** Central Power Electric Cooperative

COE Corps of Engineers **CONS TEL** Consolidated Telephone CONT RES Continental Resource Inc CPR Canadian Pacific Railway DOE Department Of Energy DAK CARR Dakota Carrier Network DAK CENT TEL Dakota Central Telephone DAK RWD Dakota Rural Water District DGC Dakota Gasification Company

DICKEY R NET Dickey Rural Networks

DICKEY RWU Dickey Rural Water Users Association DICKEY TEL Dickey Telephone

DNRR Dakota Northern Railroad DOME PL Dome Pipeline Company

DVELEC Dakota Valley Electric Cooperative Dakota, Missouri Valley & Western DVMW **ENBRDG** Enbridge Pipelines Incorporated

ENVENTIS Enventis Telephone Falkirk Mining Company FALK MNG

FHWA Federal Highway Administration Grand Forks-traill Water District G FKS-TRL WD **GETTY TRD & TRAN** Getty Trading & Transportation Golden West Electric Cooperative GLDN W ELEC Griggs County Telephone **GRGS CO TEL**

GT PLNS NAT GAS Great Plains Natural Gas Company HALS TEL Halstad Telephone Company

IDEA1 Idea1

INT-COMM TEL Inter-Community Telephone Company KANEB PL Kaneb Pipeline Company

KEM ELEC Kem Electric Cooperative Incorporated **KOCH GATH SYS** Koch Gathering Systems Incorporated

LKHD PL Lakehead Pipeline Company

LNGDN RWU Langdon Rural Water Users Incorporated

LWR YELL R ELEC Lower Yellowstone Rural Electric McKenzie Consolidated Telcom MCKNZ CON McKenzie Electric Cooperative MCKNZ ELEC

MCKNZ WRD McKenzie County Water Resource District

MCLEOD McLeod USA

McLean Electric Cooperative MCLN ELEC MCLN-SHRDN R WAT McLean-Sheridan Rural Water

MDU Montana-dakota Utilities MID-CONT CABLE Mid-Continent Cable

MIDSTATE TEL Midstate Telephone Company MINOT CABLE Minot Cable Television Minot Telephone Company MINOT TEL Missouri West Water System MISS W W S

MNKOTA PWR Minnkota Power

MOR-GRAN-SOU ELEC Mor-gran-sou Electric Cooperative MOUNT-WILLIELEC Mountrail-williams Electric Cooperative

MRE LBTY TEL Moore & Liberty Telephone MUNICIPAL City Water And Sewer City Of '..... MUNICIPAL

North Central Electric Cooperative N CENT ELEC North Valley Water District N VALL W DIST ND PKS & REC North Dakota Parks And Recreation ND TEL North Dakota Telephone Company NDDOT North Dakota Department of Transportation

NDSU SOIL SCIDEPT NDSU Soil Science Department

NEMONT TEL Nemont Telephone

NODAK R ELEC Nodak Rural Electric Cooperative NOON FRMS TEL Noonan Farmers Telephone Company

NPR Northern Plains Railroad NSP Northern States Power

NTH PRAIR RW Northern Prairie Rural Water Association

NTHN BRDR PL Northern Border Pipeline

NTHN PLNS ELEC Northern Plains Electric Cooperative Incorporated

NTHWSTRN REF Northwestern Refinery Company NW COMM Northwest Communication Cooperation

ONEOK Oneok gas

Occupational Safety and Health Administration OSHA

OTTR TL PWR Otter Tail Power Company PLEM Prairielands Energy Marketing Polar Communications POLAR COM

PVT ELEC Private Electric OWEST **Qwest Communications R&T W SUPPLY** R & T Water Supply Association RAMSEY R SEW Ramsey Rural Sewer Association Ramsey Rural Water Association RAMSEY RW RAMSEY UTIL Ramsey County Rural Utilities

RED RIV TEL Red River Rural Telephone **RESVTN TEL** Reservation Telephone ROBRTS TEL Roberts Company Telephone R-RIDER ELEC Roughrider Electric Coop Red River Valley & Western Railroad RRVW RSR ELEC R.S.R. Electric Cooperative SEWU South East Water Users Incorporated SCOTT CABLE Scott Cable Television Dickinson SHERDN ELEC Sheridan Electric Cooperative SHEYN VLY ELEC Sheyenne Valley Electric Cooperative

SKYTECH Skyland Technologies Incorporated SLOPE ELEC Slope Electric Cooperative Incorporated SOURIS RIV TELCOM Souris River Telecommunications ST WAT COMM

State Water Commission STATE LN WATER State Line Water Cooperative

STER ENG Sterling Energy

STUT RWU Stutsman Rural Water Users SW PL PRJ Southwest Pipeline Project **Turtle Mountain Communications** TMC

TCI of North Dakota TCL

TESORO HGH PLNS PL Tesoro High Plains Pipeline TRI-CNTY WU Tri-County Water Users Incorporated TRL CO RWU Traill County Rural Water Users

UNTD TEL United Telephone **UPPR SOUR WUA** Upper Souris Water Users Association U.S. Sprint

US SPRINT USAF MSL CABLE

XLENER

U.S.A.F. Missile Cable US Fish and Wildlife Service USFWS **USW COMM** U.S. West Communications VRNDRY ELEC Verendrye Electric Cooperative W RIV TEL West River Telephone Incorporated WEB W. E. B. Water Development Association

WILLI RWA Williams Rural Water Association WILSTN BAS PL Williston Basin Interstate Pipeline Company Walsh Water Rural Water District

WLSH RWD **WOLVRTN TEL** Wolverton Telephone

Xcel Energy

YSVR Yellowstone Valley Railroad

	NORTH DAKOTA					
DEPART	MENT OF TRANSPORTATION					
	07-01-14					
	REVISIONS					
DATE	DATE CHANGE					

This document was originally issued and sealed by Roger Weigel. Registration Number PE-2930. on 07/01/14 and the original document is stored at the North Dakota Department of Transportation

Line Styles D-101-20

	Line Style	es	D-101-20
Limits of Const Transition Line	— s — s — Floating Silt Curtain	Existing Aggregate (Cross Section View)	Existing Centerline
····· Bale Check	——— T —— Existing Telephone Line	Existing Curb and Gutter (Cross Section View	y) ——————— Supplemental Contour
····· Rock Check	——— TV ——— Existing TV Line	—— —— —— Existing Riprap	
····· Sight Distance Triangle Line	void — void — void — v Existing Assumed Ground (Not Surveyed)	—— —— Existing Underground Vault or Lift Station	
Small Hidden Object	void — void — void — v Tentative Ground Line	——— Tangent Line	——————————————————————————————————————
— — — — — — — — Dimension Leader	——— w ——— Existing Water or Steam Line	Hidden Object	- · · - · - · - · · - · - · - · - · Failure Line
Existing Ground	Existing Under Drain		—— —— —— Existing Conditions
Existing Topsoil (Cross Section View)		—— —— —— – Existing Conduit	—— —— —— - Existing Ground (Details)
Large Hidden Object		—— — Topsoil Profile	Existing Sixteenth Section Line
—— —— —— Edge Drain	Existing Slotted Drain	————————— Existing Conductor	Existing Right of Way Not State Owned
D D Geotextile Fabric Type D	+ + + Existing Cemetary Boundary	————————— Conductor	Phantom Object
Existing Electrical	Centerline Pavement Marking	——————— Fiber Optic	— - — - — - — Centerline Main
F0 Existing Fiber Optic Line	Barrier with Centerline Pavement Marking	Existing Loop Detector	—·—·—·—·—· Existing Guardrail Cable
F0 Existing TV Fiber Optic	Barrier Pavement Marking	——————————————————————————————————————	• • Existing Guardrail Metal
——— G —— Existing Gas Pipe	Stripe 4 IN Dotted Extension White	——————————————————————————————————————	
Geo - Geogrid	Stripe 8 IN Dotted Extension White	——————————————————————————————————————	— — — — — Excavation Limits
——— OH —— Existing Overhead Utility Line	Stripe 8 IN Lane Drop	——————————————————————————————————————	
——— P —— Existing Power		——————————————————————————————————————	· · · · · · Existing Adjacent Block Lines
———— PL ——— Existing Fuel Pipeline	Existing Box Culvert Bridge	Existing State or International Line	· · · · · · Existing Adjacent Lot Lines
Existing Undefined Above Ground Pipe Line	Existing Concrete Surface		· · · · · · Existing Adjacent Property Line
R — R Geotextile Fabric Type R	Existing Drainage Structure	Existing County	Existing Adjacent Subdivision Lines
R — R — Geotextile Fabric Type R1	Easement	Existing Section Line	NORTH DAKOTA DEPARTMENT OF TRANSPORTATION 07-01-14 This document was originally
— REMOVE — REMOVE — Remove Line	Existing Concrete	Existing Township	REVISIONS issued and sealed by DATE CHANGE Roger Weigel, Registration Number
	Existing Easement	—— — Existing Railroad Centerline	Registration Number PE- 2930, on 07/01/14 and the original
——— s ——— s —— Geotextile Fabric Type S	——— Existing Gravel Surface	—— – — Centerline	document is stored at the North Dakota Department
			of Transportation

D-101-21

	Line Styles				
	Subgrade Reinforcement	•	Existing Railroad Switch		Sheet Piling
	Existing Down Guy Wire Down Guy	•	Overhead Sign Structure Cantilever	R R R R R R	W-Beam w Posts
X X	Existing Fence		24 Inch Pipe	<u> </u>	Existing W-Beam Guardrail with Posts
	Existing Railroad		Reinforced Concrete Pipe		Exst Wet Area-Vegetation Break
======================================	Existing Sanitary Sewer	T	Signal Head with Mast Arm	<u></u>	Existing Wetland Delineated
SAN FM	Existing Sanitary Force Main	f	Existing Signal Head with Mast Arm		
======================================	Existing Storm Drain	+++++++++++++++++++++++++++++++++++++++	Tie Bar at Random Spacing		
SD FM	Existing Storm Drain Force Main		3-Cable w Posts		
xxx	Fence		Existing 3-Cable w Posts		
xxx	Silt Fence		Site Boundary		
	Existing Field Line		Fiber Rolls		
→ → ·	Exst Flow		Doweled Joint		
~ · ·	Flow		Tie Bar 30 Inch 4 Foot Center to Center		
	Existing Culvert		Tie Bar 18 Inch 3 Foot Center to Center		
	Existing Curb		Existing Berm, Dike, Pit, or Earth Dam		
	Existing Valley Gutter		Existing Ditch Block		
	Existing Driveway Gutter		Depression Contours		
<u></u>	Existing Curb and Gutter		Existing City Corporate Limits or Reservation Bo	undary	
=======================================	Existing Mountable Curb and Gutter	***************************************	Gravel Pit - Borrow Area		
•	Existing Double Micro Loop Detector		Existing Tree Boundary		
•	Micro Loop Detector Double		Tree Row		
•	Existing Overhead Sign Structure	***************************************	Existing Brush or Shrub Boundary		
•	Existing Micro Loop Detector		Existing Retaining Wall		
•	Micro Loop Detector		Existing Planter or Wall		
•	Existing Overhead Sign Structure Cantilever		Retaining Wall (Plan View)		

	NORTH DAKOTA			
DEPARTMENT OF TRANSPORTATION				
	07-01-14			
REVISIONS				
DATE	CHANGE			

This document was originally issued and sealed by Roger Weigel, Registration Number PE- 2930, on 07/01/14 and the original document is stored at the North Dakota Department of Transportation

D-101-30 Symbols \triangle North Arrow (Half Scale) Attenuation Device Existing Railroad Battery Box 0 Existing Delineator Type E Existing Bush or Shrub Truck Mounted Attenuator \vdash Diamond Grade Delineator Type A 0 \triangle Existing EFB Misc (L Type I Barricade \vdash Diamond Grade Delineator Type B ٦ Existing Flashing Beacon Existing Gas Cap or Stub \bigcirc Diamond Grade Delineator Type C ٦ Existing Pipe Mounted Flasher Type II Barricade # Existing Sanitary Cap or Stub Type III Barricade \bigcirc Diamond Grade Delineator Type D Existing Storm Drain Cap or Stub Existing Pad Mounted Feed Point (1) Catch Basin 0 Diamond Grade Delineator Type E Existing Water Cap or Stub 0.0 Existing Pipe Mounted Feed Point with Pad Flexible Delineator Cairn or Stone Circle (C) **Existing Sanitary Cleanout** Existing Pole Mounted Feed Point Video Detection Camera Flexible Delineator Type A 0 **Existing Concrete Foundation** Existing Railroad Frog \bigcirc Storm Drain Cap or Stub Flexible Delineator Type B Existing Traffic Signal Controller Existing Snow Gate 18 ◁ Corrugated Metal End Section 18 Inch Flexible Delineator Type C \subseteq Existing Pad Mounted Signal Controller Existing Snow Gate 28 Corrugated Metal End Section 24 Inch 0 Flexible Delineator Type D Existing Sixteenth Section Corner Existing Snow Gate 40 Θ 0 1 Corrugated Metal End Section 30 Inch Flexible Delineator Type E Existing Headwall Existing Quarter Section Corner \oplus Corrugated Metal End Section 36 Inch Existing Pedestrian Head with Number \vdash Delineator Type A **Existing Section Corner** \bigcirc Corrugated Metal End Section 42 Inch \vdash Delineator Type A Reset Existing Railroad Crossbuck Existing Signal Head

Existing Sprinkler Head Corrugated Metal End Section 48 Inch \vdash Delineator Type B Existing Satellite Dish Þ Concrete Foundation \vdash Delineator Type B Reset Existing Fuel Dispensers Q Existing Fire Hydrant ((()) **Ground Connection Conductor** # Delineator Type C Existing Flexible Delineator Type A Existing Catch Basin Drop Inlet Neutral Connection Conductor \bigcirc Delineator Type D Existing Flexible Delineator Type B Existing Curb Inlet OID Phase 1 Connection Conductor **(3)** Delineator Type E Existing Flexible Delineator Type C **Existing Manhole Inlet** Phase 2 Connection Conductor Delineator Drums 0 Existing Flexible Delineator Type D **Existing Junction Box**

(3)

0

Existing Flexible Delineator Type E

Existing Delineator Type A

Existing Delineator Type B

Existing Delineator Type C

Existing Delineator Type D

Spot Elevation

Existing Artifact

₳

(

•

Existing Access Control Arrow

Existing Flashing Beacon

Existing Benchmark

Traffic Cone

Signal Controller

Alignment Data Point

Pad Mounted Signal Controller

Emergency Vehicle Detector

 \bigcirc

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION					
	07-01-14				
	REVISIONS				
DATE	CHANGE				

This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 07/01/14 and the original document is stored at the North Dakota Department of Transportation

D-101-31 Symbols 0 Existing Light Standard (⊗) Existing Manhole with Valve Water 0 Existing Telephone Pole (_) Existing Undefined Manhole (\bigcirc) (3) Existing High Mast Light Standard 10 Luminaire Existing Water Manhole Existing Wood Pole Existing Undefined Pull Box Ω Existing High Mast Light Standard 3 Luminaire Existing Mile Post Type A Existing Post Existing Undefined Pedestal Existing High Mast Light Standard 4 Luminaire Existing Mile Post Type B Existing Pedestrian Push Button Post Existing Undefined Valve Existing High Mast Light Standard 5 Luminaire Existing Mile Post Type C Δ Existing Control Point CP Existing Undefined Pipe Vent Existing Control Point GPS-RTK Existing High Mast Light Standard 6 Luminaire Existing Reference Marker Δ Existing Gas Valve Existing High Mast Light Standard 7 Luminaire Existing RW Marker ◬ **Existing Control Point TRI** Existing Water Valve (D) Existing High Mast Light Standard 8 Luminaire Existing Utility Marker \triangle Existing Reference Marker Point NGS Existing Fuel Pipe Vent (8) Existing Gas Pipe Vent Existing High Mast Light Standard 9 Luminaire 0 Iron Monument Found Existing Pull Box \otimes Existing Overhead Sign Structure Load Center Iron Pin R/W Monument Existing Intelligent Transportation Pull Box Existing Sanitary Pipe Vent 7 Existing Object Marker Type I ø Existing Water Pump Existing Storm Drain Pipe Vent **Existing Luminaire** Existing Object Marker Type II Existing Light Standard Luminaire k OID Existing Slotted Reinforced Concrete Pipe Existing Water Pipe Vent Existing Federal Mailbox Existing Object Marker Type III Existing RR Profile Spot **Existing Weather Station** Existing Private Mailbox Ω Existing Electrical Pedestal Existing Fuel Leak Sensors Existing Ground Water Well Bore Hole \boxtimes \oplus Ω Existing Windmill or Tower Existing Meander Section Corner Existing Telephone Pedestal Existing Highway Sign \oplus Existing Meter П Existing Fiber Optic Telephone Pedestal Existing Miscellaneous Spot Existing Witness Corner (_) Ω ¤ Existing Electrical Manhole Existing TV Pedestal Existing Lighting Standard Pole Flashing Beacon (\bigcirc) Existing Gas Manhole П Existing Fiber Optic TV Pedestal 0 Existing Traffic Signal Standard Flagger \Box (\bigcirc) \bigcirc Existing Sanitary Manhole • Existing Fuel Filler Pipes A **Existing Transformer** Θ (_) Existing Sanitary Force Main Manhole Δ Existing Traverse PI Aerial Panel Existing Large Evergreen Tree \times (⊗) Existing Sanitary Manhole with Valve \circ Existing Pole Existing Small Evergreen Tree nt was originally (_) Existing Storm Drain Manhole Existing Large Tree d sealed by -**Existing Power Pole** Weigel, £3 (_) Existing Force Main Storm Drain Manhole 8 Existing Power Pole with Transformer Existing Small Tree

Existing Tree Trunk

Existing Pad Mounted Traffic Signal Control Box

 \subseteq

(⊗)

(_)

Existing Force Main Storm Drain Manhole with Valve

Existing Telephone Manhole

) [Pipe Mounted Flasher	
;	Sanitary Force Main with	Valve
DEPARTM	NORTH DAKOTA MENT OF TRANSPORTATION	
	07-01-14	This document
	REVISIONS	issued and
DATE	CHANGE	Roger '
		Registration
		PE- 2
		on 07/01/14 a
		document is
		North Dakota
		of Trans
•		


ion Number 2930, and the original stored at the ta Department sportation


Symbols D-101-32


			Symbols				D-101-32
П	Pad Mounted Feed Point	-	Light Standard 1000 Watt High Pressure Sodium Vapor Luminair	e k	Object Marker Type I		Reinforced Concrete End Section 48 Inch
0 0	Pipe Mounted Feed Point with Pad	→	Light Standard 150 Watt High Pressure Sodium Vapor Luminaire	k	Object Marker Type II		Reinforced Concrete End Section 54 Inch
\bigcirc	Pole Mounted Feed Point	─ ♦	Light Standard 175 Watt High Pressure Sodium Vapor Luminaire	 k	Object Marker Type III	(D)	Reset Right of Way Marker
<u>į</u>	Headwall	-	Light Standard 200 Watt High Pressure Sodium Vapor Luminaire		Caution Mode Arrow Panel	•	Reset USGS Marker
	Double Headwall with Vegitation Barrier	-	Light Standard 250 Watt High Pressure Sodium Vapor Luminaire	П	Back to Back Vertical Panel Sign	(9)	Right of Way Markers
	Single Headwall with Vegitation Barrier	—	Light Standard 310 Watt High Pressure Sodium Vapor Luminaire	\bigoplus_{\blacksquare}	Double Direction Arrow Panel	0	Riser 30 Inch
•	Pole Mounted Head	-O	Light Standard 35 Watt High Pressure Sodium Vapor Luminaire		Left Directional Arrow Panel	CSB	Continuous Split Barrel Sample
	Sprinkler Head	-	Light Standard 400 Watt High Pressure Sodium Vapor Luminaire	\Rightarrow	Right Directional Arrow Panel	EA .	Flight Auger Sample
•	Fire Hydrant	\rightarrow	Light Standard 50 Watt High Pressure Sodium Vapor Luminaire	ooo	Sequencing Arrow Panel	N S B	Split Barrel Sample
Ш	Inlet Type 1	—	Light Standard 70 Watt High Pressure Sodium Vapor Luminaire		Truck Mounted Arrow Panel	Ŀ	Thinwall Tube Sample
	Inlet Type 2	-	Light Standard 700 Watt High Pressure Sodium Vapor Luminaire	-	Power Pole	‡	Highway Sign
	Double Inlet Type 2	0	Manhole		Wood Pole	0 .	SNOW GATE 18 FT
Ш	Inlet Grate Type 2	O	Manhole 48 Inch	•	Pedestrian Push Button Post	O .	SNOW GATE 28 FT
	Junction Box	0	Sanitary Force Main Manhole	•	Property Corner	0 .	SNOW GATE 40 FT
	High Mast Light Standard 10 Luminaire	0	Sanitary Sewer Manhole	\otimes	Pull Box	Z	Standard Penetration Test
	High Mast Light Standard 3 Luminaire	0	Storm Drain Manhole	\otimes	Intelligent Transportation Pull Box	A	Transformer
	High Mast Light Standard 4 Luminaire	(11)	Storm Drain Manhole with Inlet	ø	Sanitary Pump	Incl	Inclinometer Tube
	High Mast Light Standard 5 Luminaire	þ	Reset Mile Post	ø	Storm Drain Pump	0	Underdrain Cleanout
	High Mast Light Standard 6 Luminaire	þ	Mile Post Type A		Reinforced Pavement		Excavation Unit
	High Mast Light Standard 7 Luminaire	þ	Mile Post Type B	В	Reinforced Concrete End Section 15 Inch	⊖	Water Valve
	High Mast Light Standard 8 Luminaire	l -	Mile Post Type C	В	Reinforced Concrete End Section 18 Inch	DEPAR	NORTH DAKOTA MENT OF TRANSPORTATION This document was originally
	High Mast Light Standard 9 Luminaire	(11)	Right of Way Marker	\forall	Reinforced Concrete End Section 24 Inch	DATE	O7-01-14 REVISIONS CHANGE This document was originally issued and sealed by Roger Weigel,
	Relocate Light Standard	•-	Tubular Marker	\forall	Reinforced Concrete End Section 30 Inch		Registration Number PE- 2930 ,
	Overhead Sign Structure Load Center	•	Alignment Monument		Reinforced Concrete End Section 36 Inch		on 07/01/14 and the original document is stored at the North Dakota Department
- ♦	Light Standard 100 Watt High Pressure Sodium Vapor Luminaire	•	Iron Pin Reference Monument		Reinforced Concrete End Section 42 Inch		of Transportation


BREAKAWAY SYSTEMS FOR CONSTRUCTION ZONE SIGNS

Perforated Tube











Top Post Receiver Plate - ASTM A572 grade 50 Angle Receiver - 2½"x2½"x¾" ASTM A36 structural angle



Bottom Soil Stub Tube - 3"x3"x7 gauge ASTM A500 grade B tube Stabilizing Wing - 7 gauge H.R.P.O. ASTM A1011 Plate - ASTM A572 grade 50



Bolt Retainer for Base Connection Bolt Retainer- 1/32" Reprocessed Teflon

- 1. Slip base bolts shall be torqued as specified by the manufacturer.
- 2. Anchor shall have a yield strength of 43.9 KSI and tensile strength of 59.3 KSI.
- 3. The 4" vertical clearance is required for the anchor or breakaway base. The 4"x60" measurement shall be made above and below post location and also back and ahead of the post.
- 4. When used in concrete sidewalk, anchor shall be same except without the wings.
- 5. Four post signs shall have over 7' between the first and the fourth posts.

	Telescoping Perforated Tube						
Number of Posts	Post Size in.	Wall Thick- ness Gauge	Sleeve Size in.	Wall Thick- ness Gauge	Slip Base	Anchor Size without Slip Base in.	
1	2	12			No	21/4	
1	21/4	12			No	2½	
1	2½	12			(A)	3	
1	2½	10			Yes		
1	21/4	12	2	12	Yes		
1	2½	12	21/4	12	Yes		
2	2	12			No	21/4	
2	21/4	12			No	2½	
2	2½	12			Yes		
2	2½	12			Yes		
2	21/4	10	2	12	Yes		
2	2½	12	21/4	12	Yes		
3 & 4	2½	12			Yes		
3 & 4	2½	10			Yes		
3 & 4	2½	12	21/4	12	Yes		
3 & 4	21/4	12	2	12	Yes		
3 & 4	2½	10	2¾6	10	Yes		

	Properties of Telescoping Perforated Tube							
Tube Size In.	Wall Thickness in.	U.S. Standard Gauge	Weight per Foot lbs	Moment of Inertia in.4	Cross Sec. Area in.²	Section Modulus in.3		
1½ x 1½	0.105	12	1.702	0.129	0.380	0.172		
2 x 2	0.105	12	2.416	0.372	0.590	0.372		
2¼ x 2¼	0.105	12	2.773	0.561	0.695	0.499		
2¾ ₆ x 2¾ ₆	0.135	10	3.432	0.605	0.841	0.590		
2½ x 2½	0.105	12	3.141	0.804	0.803	0.643		
2½ x 2½	0.135	10	4.006	0.979	1.010	0.785		

Top Post Receiver Data Table						
Square Post Sizes (B)	А	В	С	D	Е	F
2¾ ₁₆ "x10 ga.	1%4"	2½"	31/32"	²⁵ / ₃₂ "	1 ³ % ₄ "	1%"
2½"x10 ga.	1%2"	2½"	35⁄16"	5%"	1 ² / ₃₂ "	1¾"


- (A) The breakaway base is required when the support is placed in weak soils. The Engineer shall determine if the soils are weak.
- (B) The $2\frac{3}{16}$ "x10 ga. may be inserted into $2\frac{1}{2}$ "x10 ga. for additional wind load.


NORTH DAKOTA DEPARTMENT OF TRANSPORTATION				
	2-28-14			
REVISIONS				
DATE	CHANGE			

This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 2/28/14 and the original document is stored at the North Dakota Department of Transportation


BREAKAWAY SYSTEMS FOR CONSTRUCTION ZONE SIGNS

U-Channel Post






Breakaway U-Channel Detail Alternate A A maximum of 2 posts shall be installed within 7'.



Retainer Strap Detail



Breakaway U-Channel Splice Detail Alternate B (2.5 and 3 lb/ft) A maximum of 3 posts shall be installed within 7'.

2- bolts grade 5, lock nuts and lock washers

2- bolts grade 5, lock nuts and lock washers

4 Anchor unit (42" min.)

Breakaway U-Channel Splice Detail
Alternate C
(2.5 and 3 lb/ft)

A maximum of 3 posts shall be installed within 7'.

Alternate A Steps of Installation:


- a) Drive anchor unit to within 12" of ground level.
 b) Proper assembly established by lining up the bottom hole of retainer strap with the 6th hole from the top of the anchor unit.
 c) Assemble strap to back of anchor unit using 5/16"x2" bolt, lock washer and nut.
 d) Rotate strap 90" to left.
- a) Drive anchor unit to 4" above ground.
 b) Rotate strap to vertical position.
- a) Place 5/6"x2" bolt, lock washer and nut in bottom of sign post to facilitate alignment of sign post with proper hole in anchor unit.
 b) Alternately tighten two connector bolts.
- 4. Complete assembly by tightening $\frac{1}{16}$ "x2" bolt (this fastens sign post to retainer strap).
- The base post, strap and sign post shall be properly nested. Proper nesting occurs when all flat surfaces of the base post, strap, and sign post at the boits have full contact across the entire width.


	NORTH DAKOTA				
DEPARTM	MENT OF TRANSPORTATION				
	2-28-14				
	REVISIONS				
DATE	CHANGE				


This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 2/28/14 and the original document is stored at the North Dakota Department of Transportation


CONSTRUCTION SIGN DETAILS TERMINAL AND GUIDE SIGNS





















ARROW DETAILS


(A) Arrow may be right or left of the legend to indicate construction to the right or left.

DEPARTI	NORTH DAKOTA MENT OF TRANSPORTATION	
	8-13-13	
	REVISIONS	
DATE	CHANGE	
		(

This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 8/13/13 and the original document is stored at the North Dakota Department of Transportation
















Legend: black (non-refl) Background: orange


CONSTRUCTION SIGN DETAILS REGULATORY SIGNS




Legend: black (non-refl) Background: white










R11-2a-48 Legend: black (non-refl) Background: white


		NORTH DAKOTA DEPARTMENT OF TRANSPORTATION			
s document wa	Thi:		8-13-13		
issued and sea		S	REVISION		
Roger Wei		HANGE	CH	DATE	
Registration N					
PE- 2930					
8/13/13 and	on				
ocument is stor	d				
orth Dakota De	N				
of Transport					

as originally ealed by eigel, Number 30, I the original ored at the epartment rtation


D-704-11




Legend: black (non-refl) Background: orange



CONSTRUCTION SIGN DETAILS




6"C 12"




WORD LETTER SPACING AHEAD Standard 200 FT Standard 350 FT Standard Standard 1000 FT Reduce 40% 1500 FT Reduce 40% ½ MILE Reduce 50% 1 MILE Standard

* DISTANCE MESSAGES




Legend: black (non-refl) Background: orange



ARROW DETAILS

R 3" 1½" 3½" 11115½6"—1	R 3" 11/4" 3/4" 11/5/16" 11/5/16" 11/5/16"
TRUCKS 15%" 15%" 6°C 3½"	TRUCKS - 12% - 12% - 3%"
15 [%] ₁ " 15 [%] ₁₆ " 3 ¹ / ₂ "	<u>12¾6"</u> 12½" → 12½" → 13½"
FNTFRING 6°C	6"C
14" 13%"	14"13%"1 3½"
HIGHWAY 2½" 6"C	HIGHWAY 6°C
	48"
W8-53-48	W8-56-48


Legend: black (non-refl) Background: orange




Background: orange

	NORTH DAKOTA				
DEPARTM	MENT OF TRANSPORTATION				
	8-13-13				
REVISIONS					
DATE CHANGE					

This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 8/13/13 and the original document is stored at the North Dakota Department of Transportation





NOTES:

 Sign Supports: Supports shall be galvanized or painted. Minimum post sizes are 2.5 lb/ft u-channel or 2" x 2" x 12 gauge steel perforated tube, except where noted. When installing signs on u-channel, the minimum post size for assemblies containing a secondary sign is 3.0 lb/ft. Post sizes are based on a wind speed of 55 MPH.

Signs over 50 square feet should be installed on $2 \frac{1}{2}$ x $2 \frac{1}{2}$ perforated tube supports as a minimum.

Guy wires shall not be attached to sign supports. Wind beams may be attached to u-posts behind the sign panels.

- 2. Sign Panels: Provide sign panels made of 0.100" aluminum, $\frac{1}{2}$ " plywood, or other approved material, except where noted. All holes to be punched round for $\frac{1}{2}$ " bolts.
- Alternate Messages: The signs that have alternate messages may have these alternate messages placed on a reflectorized plate (without a border) and installed and removed as required. (i.e. "Left" and "Right" message on a lane closure sign)
- Route Marker Auxiliary Signs: Provide route marker auxiliary signs, such as the cardinal direction and directional arrows, with a background and legend that match the route marker they are used with:

Interstate - white legend on blue background Interstate Business Loop - white legend on green background US and State - black legend on white background County - yellow legend on blue background

5. Vertical Clearance: Install signs with a vertical clearance of 5'-0" (see TYPICAL SECTION.) In areas where parking or pedestrian movements are likely or the view of the sign may be obstructed, install signs with a vertical clearance of 7'-0" from the top of the curb or from the near edge of the driving lane in absence of a curb.

The vertical clearance to secondary signs is 1'-0" less than the vertical clearance as stated above

Large signs having an area exceeding 50 square feet shall have a minimum clearance of 7'-0" from the ground at the post.

Portable Signs: Provide portable signs that meet the vertical clearance as stated above. Use portable signs when it is necessary to place signs within the pavement surface.

When portable signs are used for 5 days or less, low-mounting height (minimum 12" vertical clearance) sign supports may be used as long as the view of the sign is not obstructed. Time delays caused by unforseen circumstances, such as equipment breakdown, rain, subgrade failures, etc., will not accrue towards the 5 day period. The R9-8 through R9-11a series, W1-6 through W1-8 series, M4-10, and E5-1 may be used for longer than 5 days.

Signs mounted to the portable sign supports shown in the LOW-MOUNTING HEIGHT and HIGH-MOUNTING HEIGHT Details shall have a maximum surface area of 16 square feel

MINIMUM BALLAST (For each side of sign support base)

Sign Panel Mounting Height (ft)	Number of 25 lb sandbags for 4' x 4' sign panel
1'	6
5'	8
7'	10

Note: The number of sandbags are based on a wind speed of 55 MPH. The sandbags are assumed to be placed at or near the ends of the skids.


NORTH DAKOTA
DEPARTMENT OF TRANSPORTATION

10-4-13
REVISIONS
DATE CHANGE


11-14-13 Revised Note 6.

This document was originally issued and sealed by Roger Weigel, Registration Number PE- 2930, on 11/14/13 and the original document is stored at the North Dakota Department

of Transportation




CONSTRUCTION TRUCK AND TEMPORARY DETOUR LAYOUTS



Notes

- Barricades placed on roadway shall be on a moveable assembly.

 Signs placed on the roadway shall be placed on skid mounted assemblies.
- 2. Where necessary, safe speed to be determined by the Engineer.
- 3. The reduced speed limit shall be determined dependent on the in place speed limit before construction. The speed limit reduction should not exceed 10 mph below the existing speed limit, unless the design speed of the work zone feature has been reduced below the 10 mph. In this case, the speed limit reduction shall not exceed 30 MPH. Where speed limits are to be reduced more than 30 MPH, a second speed limit sign shall be installed with the desired speed reduction but shall not exceed 30 MPH. The second speed limit sign shall be placed at ½ B.
- 4. When warning signs are used in urban areas and the signs are not portable, flags shall be installed. The flags shall be 24 inches square, mounted perpendicular to the edges of the diamond sign, and at such a distance above the edge so that when the flag is limp it will not touch the sign. Rural areas will not require flags.
- 5. Existing speed limit signs within a reduced speed zone shall be covered.
- 6. Obliterated or covered pavement marking shall be paid for as Obliteration of Pavement Marking. The covering shall be approved by the engineer.
- 7. The contractor has the option of using portable sign supports in lieu of post mounted signs in accordance with the NDDOT Standard Specifications.
- 8. The contractor shall install the G20-1b-60 sign when work is suspended for winter.
- 9. If existing stop sign is in place, a 48" stop sign is not required.
- 10. G20-55-96 sign is not required if this standard is part of other traffic control layouts with this sign or the work is less than 15 days.



ADVANCE WARNING SIGN SPACING					
Road Type		Distance Between Signs Min. (ft)			
		В	С		
Urban - Low Speed (30 mph or less)	150	150	150		
Urban - Low Speed (over 30 to 40mph)	280	280	280		
Urban - High Speed (over 40 mph to 50 mph)	360	360	360		
Rural - High Speed (over 50 mph to 65 mph)	720	720	720		
Urban Expressway and Freeway (55 mph to 60 mph)	850	1350	2200		
Rural Expressway and Freeway (70 mph to 75 mph)	1000	1500	2640		
Interstate/4-Lane Divided (Maintenance and Surveying)	750	1000	1500		

	NORTH DAKOTA DEPARTMENT OF TRANSPORTATION			
	9-27-13			
ſ	REVISIONS			
	DATE	CHANGE		

This document was originally issued and sealed by Roger Weigel Registration Number PE-2930, on 09/27/13 and the original document is stored at the North Dakota Department of Transportation

Rural Expressway and Freeway

(Maintenance and Surveying)

(70 mph to 75 mph) Interstate/4-Lane Divided 1000

750

1500

1000


2640

1500


North Dakota Department

of Transportation


PAVEMENT MARKING D-762-4



Two Lane Two Way
RURAL ROADWAY




Two Lane Divided
Rural Roadway
PRIMARY HIGHWAY
Asphalt Section



Two Lane Roadway

PRIMARY HIGHWAY


Concrete Section



Two Lane Roadway

INTERSTATE HIGHWAY


Asphalt Section



Two Lane Roadway


INTERSTATE HIGHWAY

Concrete Section




RURAL FIVE LANE ROADWAY

Asphalt Section




URBAN FIVE LANE SECTION



RURAL FOUR LANE ROADWAY


Concrete Section

URBAN FOUR LANE SECTION
Concrete Section




RURAL FIVE LANE ROADWAY

Concrete Section




URBAN FIVE LANE SECTION
Concrete Section




RURAL FOUR LANE ROADWAY

Asphalt Section



URBAN FOUR LANE SECTION
Asphalt Section



CENTERLINE PAVEMENT MARKING SKIP SPACING DETAIL

NOTES:

 Edge lines shall be continued through private drives and field drives and broken for intersections.

NORTH DAKOTA		
DEPARTMENT OF TRANSPORTATION		
12-1-10		
REVISIONS		
DATE	CHANGE	

This document was originally issued and sealed by Roger Weigel, Registration Number PE- 2930, on 12-1-10 and the original document is stored at the North Dakota Department of Transportation